



MADE IN ITALY since 1972

PERFORMER P2000

NEW-MODELS

FEATURES

- # CB & 10 m Mobile antennas
- # Very High power handling
- # Tunable from 27 to 30 MHz
- # DC-Ground protection
- # 17/7 PH tapered stainless steel whip
- # PL version (suffix PL) with a special base connection suitable for magnetic mount installation (no cable supplied)

TECHNICAL DATA

Type: base loaded
 Impedance: 50 Ω
 Frequency range: 27 ... 30 MHz
 Polarization: linear vertical
 SWR @ res. freq.: ≤ 1.2
 Max. power: 2000 Watts (CW) Duty Cycle 5' on-5' off
 Bandwidth @ SWR ≤ 2: ≥ 1800 kHz (160 channel)
 Mounting:
 PERFORMER P2000 Coax hole Ø 12.5 mm, Ø 1/2 in
 PERFORMER P2000 PL UHF-male (PL 259)
 Cable length / Type:
 PL version not supplied
 Coax version: .. 4m, 13ft/standard RG58 (max power up to 600 Watts)
 Height (approx.): 1920 mm, 6.3 ft
 Weight (approx.): 730 gr, 1.6 lb

P/N 2218305.50 PERFORMER P2000 coax (standard cable)
 P/N 2218305.51 PERFORMER P2000 PL

P2000 3/8

FEATURES

- # CB & 10 m Trucker antenna
- # 17/7 PH Tapered whip 1.8m / 71"
- # 200mm / 8" Stainless Steel Shaft
- # Very high Power Handling capability

TECHNICAL DATA

Type: Trucker Antenna
 Impedance: 50 Ω
 Frequency range: 27 ... 30 MHz
 Polarization: linear vertical
 SWR @ res. freq.: ≤ 1.2
 Max. power: 1500 Watts (CW) continuous
 5000 Watts (CW) short time
 Bandwidth @ SWR ≤ 2: ≥ 2600 kHz (230 channel)
 Mounting: both model 3/8" x 24 thread
 Shaft version: shaft 200mm, 8"
 Cable length / Type: not supplied
 Height (approx.): 2080 mm, 6.8 ft
 Weight (approx.): 440 gr, 0.97 lb

P/N 2418305.03 PERFORMER P2000 3/8 w/shaft



PERFORMER P2000




OPTIONAL HI-POWER CABLE
max power up to 2000 Watts
4m, 13 ft / RG 303 PTFE cable
P/N 2509605.00


HI-POWER MATCHING COIL



Low loss dielectric support.
 Air wound big section copper wire
 Ø 2.5mm
 AWG 10



P2000 Coax (cable supplied) for fixed installation hole required



P2000 PL (no cable supplied) for UHF-female installation



PERFORMER P2000 3/8



Optional "CB-HDS" 3/8 to SO-239
P/N 2508106.00