



MADE IN ITALY since 1972

PERFORMER 5000 LED PERFORMER 5000 TURBO 5000

FEATURES

- # CB & 10 m Mobile antennas
- # Very High power handling
- # Tunable from 27 to 30 MHz
- # P5000 LED: Unique LED PCB that ligh up when transmit
- # DC-Ground protection
- # 17/7 PH tapered stainless steel whip
- # Whip detachable for car-wash
- # PL version (suffix PL) with a special base connection suitable for magnetic mount installation (no cable supplied)

TECHNICAL DATA

Type: base loaded
 Impedance: 50 Ω
 Frequency range: 27 ... 30 MHz
 Polarization: linear vertical
 SWR @ res. freq.: ≤ 1.2
 Max. power: 1500 Watts (CW) continuous
 5000 Watts (CW) short time
 Bandwidth @ SWR ≤ 2: ≥ 2300 kHz (200 channel)
 Mounting:
 TURBO-PERFORMER 5000 Coax hole Ø 12.5 mm, Ø 1/2 in
 TURBO-PERFORMER 5000 PL UHF-male (PL 259)
 Cable length / Type:
 PL version not supplied
 Coax version: .. 4m, 13ft/standard RG58 (max power up to 600 Watts)
 Height (approx.): 1965 mm, 6.4 ft
 Weight (approx.): 650 gr, 1.4 lb

- P/N 2218505.50/LED PERFORMER-5000 LED (stand. cable)
- P/N 2218505.51/LED PERFORMER-5000 PL LED
- P/N 2218505.50 PERFORMER-5000 (standard cable)
- P/N 2218505.51 PERFORMER-5000 PL
- P/N 2202205.40 TURBO-5000 (standard cable)
- P/N 2202205.43 TURBO-5000 PL

