



MADE IN ITALY since 1972

TITANIUM series

FEATURES

- # CB & 10m Mobile antennas
- # Tunable from 27 to 28.5 MHz
- # 180° adjustable whip
- # Detachable for car-wash
- # Suitable for magnetic mount

TECHNICAL DATA

Type: base loaded
 Impedance: 50 Ω
 Frequency range: 27... 28.5 MHz
 Polarization: linear vertical
 SWR @ res. freq.: ≤ 1.2
 Max. Power
 TITANIUM 800, TITANIUM 1000 15 Watts (CW) continuous
 150 Watts (CW) short time
 TITANIUM 1200 20 Watts (CW) continuous
 100 Watts (CW) short time
 TITANIUM 1500 Black 35 Watts (CW) continuous
 250 Watts (CW) short time
 Bandwidth @ SWR ≤ 2:
 TITANIUM 800 ≥ 1100 kHz (100 channel)
 TITANIUM 1000 ≥ 1200 kHz (110 channel)
 TITANIUM 1200 ≥ 1400 kHz (125 channel)
 TITANIUM 1500 Black ≥ 1600 kHz (140 channel)
 Height (approx.):
 TITANIUM 800 790 mm, 2.6 ft
 TITANIUM 1000 975 mm, 3.2 ft
 TITANIUM 1200 1215 mm, 4.0 ft
 TITANIUM 1500 Black 1420 mm, 4.6 ft
 Weight (approx.): 400 gr, 0.88 lb
 Mount type: "N" mount, hole Ø12.5mm, Ø1/2 in
 Cable length / type: 4m, 13 ft / RG58

P/N 2200605.01 or .07 TITANIUM 800 N or NE
 P/N 2204505.01 or .07 TITANIUM 1000 N or NE
 P/N 2204505.01/S or .07/S TITANIUM 1200 N or NE
 P/N 2204506.02 or .08 TITANIUM 1500 Black N or NE

P/N 2200605.61 TITANIUM 800 MAG
 P/N 2204505.61 TITANIUM 1000 MAG
 P/N 2204505.61/S TITANIUM 1200 MAG

